

# Automatic Liquid Filling Machine (Servo System)

全自動罐裝液體充填機 (伺服系統)

■ CM-L3410-S



## ■ 適用範圍：

適合充填，高、低濃稠度及易起泡沫之液體。

## ■ 特性：

1. 採用伺服馬達控制定量缸進行充填，定量精度高。
2. 容量調整只需透過人機介面調整充填數據，調整容量快速方便。
3. 出料及吸料速度穩定平順，可個別調整快慢。
4. 充填時充填管潛入瓶身充填設計，減少泡沫產生。
5. 逆止閥設計，避免充填口滴料。
6. 充填管可調整高低，適合多種高低瓶身使用。
7. 充填管路快拆式設計，清洗保養容易。
8. 液體接觸面及充填管均以 SUS.304# 配製。
9. 全機均以 SUS304#、鋁合金設計製造。

## ■ Application：

Suitable for high viscosity or flowing liquid that easy to foamy and spume.

## ■ Features：

1. Cylinder controlled by Servo Motor, high accuracy.
2. Volume adjusting by HMI, easy and fast.
3. olume adjusted by scale and individually, easy to operate.
4. Filling nozzle dip into bottle, avoid liquid foamy.
5. Check Valve designed ensure accuracy and easy to clean.
6. Height of filling nozzle is adjustable, suitable for various higher or lower bottle sizes.
7. Filling nozzle is easy to disassemble and maintain.
8. All parts that contact with liquid and filling nozzles are made by SUS.304#.
9. All parts that in contact are made of SUS.304# and with polishing process. Meet with G.M.P. Standard.

## ■ Specification 規格表

<b>Filling Range</b>	充填範圍	<b>200 c.c.~2000 c.c.</b>
<b>Filling Speed</b>	充填速度	<b>16~20 bottles/min 瓶/分</b>
<b>Accuracy</b>	精 度	<b>± 1 %</b>
<b>Power, Source</b>	電 源	<b>220/380 Volts, 3 Phase</b>
<b>Power Consumption</b>	消耗電力	<b>2.2 KW</b>
<b>Machine Size</b>	機械尺寸	<b>L2400 x W1400x H2137mm</b>



**ChangMao Machinery Industrial Co., Ltd 彰茂機械工業股份有限公司**

**No. 109-4, Sec. 3, Sian-Dong Rd., He-Mei Township, Chang Hwa Hsien, Taiwan**

**彰化縣和美鎮線東路 3 段 109-4 號 TEL: +886-4-7351151 FAX: +886-4-7351101**

**<http://www.taiwan-changmao.com.tw> e-mail: [twcm1975@gmail.com](mailto:twcm1975@gmail.com) Skype: tcm1975**