# Semi-Automatic Powder Filling Machine (Lifting System) 半自動粉末充填機 (升降系統) ■ CM-P153A

### ■ Application:

Suitable for powder of foods, Medicines, Chemicals, Pesticides...etc in Bottle.

#### ■ Features:

- Human Machine Interface Control System, Touch Screen.
  Easy to operate.
- 2. Auger driven by Servo Motor, positioning precise.
- 3. Adapt servo mixing motor, mixing speed is adjustable.
- 4. Lifting system controlled by servo motor, down and extruding speed are adjustable and match up according to the powder character.
- All parts that contact with powder are made of SUS.304# and polished, meet with G.M.P. Standard.

#### ■ 適用範圍:

適用食品類、中藥、西藥, 化工產品及農藥產品, 之罐裝粉末。

## ■ 特性:

- 1. 控制系統採用人機介面,觸控螢幕,操作容易。
- 2. 螺桿傳動系統採用伺服馬達,定位準確。
- 3. 攪拌採用伺服馬達,可依物料特性調整適合攪拌速度。
- 4. 升降系統採用伺服馬達控制,可以搭配充填原料調整適合的下降擠壓速度,將比重較輕的原料擠壓進容器裡。
- 5. 粉末接觸面均以 SUS.304#製造及拋光處理,符合 G.M.P 要求。

# ■ Specification 規格表

Filling Range	計量範圍	1~1000g
Filling Speed	充填速度	10~15 Containers/min 罐/ 分
Accuracy	精 度	± 1 %
Power Source	電 源	220 / 380 Volts, 3 Phase
Power Consumption	消耗電力	2.65 KW
Machine Size	機械尺寸	L.890 x W.995 x H.2125mm
Machine Weight	機械重量	270 KG





ChangMao Machinery Industrial Co., Ltd 彰茂機械工業股份有限公司 No. 109-4, Sec. 3, Sian-Dong Rd., He-Mei Township, Chang Hwa Hsien, Taiwan 彰化縣和美鎮線東路 3 段 109-4 號 TEL: +886-4-7351151 FAX: +886-4-7351101 http://www.taiwan-changmao.com.tw e-mail: twcm1975@gmail.com Skype: tcm1975