

Semi-Automatic Liquid Filling Machine (4 nozzles)

半自動液體充填機 (4 支頭式)

■ CM-L1410-A

■ Application :

Suitable for high viscosity or flowing liquid that easy to foamy and spume.

■ Features :

1. Filling by air cylinder driven with quantitative cylinder.
2. Filling speed stable and smoothly, it can be adjust separately.
3. Volume adjusted by scale, easy to operate.
4. Filling nozzle dip into bottle, avoid liquid foamy.
5. Check Valve designed ensure accuracy and easy to clean.
6. Height of filling nozzle is adjustable, suitable for various higher or lower bottle sizes.
7. Filling nozzle is easy to disassemble and maintain.
8. All parts that contact with liquid and filling nozzles are made by SUS.304#.

PS: 1. Please prepare air compressor when use this machine.

■ 適用範圍 :

適合高、低濃稠度及易起泡沫之液體。

■ 特性 :

1. 採用空壓缸方式帶動定量缸進行充填動作。
2. 出料及吸料速度穩定平順，可個別調整快慢。
3. 容量調整只需依照刻度表簡易調整所需充填容量。
4. 充填時充填管潛入瓶身充填設計，減少泡沫產生。
5. 逆止閥設計，避免充填口滴料。
6. 充填管可調整高低，適合多種高低瓶身使用。
7. 充填管路快拆式設計，清洗保養容易。
8. 液體流經接觸面及充填管均以 SUS.304# 配制。

附註：1. 需自備空壓機。

■ Specification 規格表

Filling Range	充填範圍	200 c.c. ~ 1000 c.c
Filling Speed	充填速度	16~20 bottles/min 瓶/分
Accuracy	精 度	± 1%
Power, Source	電 源	220/380 Volts, 3 Phase
Power Consumption	消耗電力	0.1 KW
Machine Size	機械尺寸	L.1000 x W.1120 x H.1990mm



ChangMao Machinery Industrial Co., Ltd 彰茂機械工業股份有限公司

No. 109-4, Sec. 3, Sian-Dong Rd., He-Mei Township, Chang Hwa Hsien, Taiwan

彰化縣和美鎮線東路 3 段 109-4 號 TEL: +886-4-7351151 FAX: +886-4-7351101

<http://www.taiwan-changmao.com.tw> e-mail: twcm1975@gmail.com Skype: tcm1975